

type number		width of cable tray (A)
KL 60X150_S	KL 60X150_F	150
KL 60X200_S	KL 60X200_F	200
KL 60X300_S	KL 60X300_F	300
KL 60X400_S	KL 60X400_F	400
KL 60X500_S	KL 60X500_F	500
KL 60X600_S	KL 60X600_F	600

height of cable ladder: 60 mm

length of cable ladder: 3000 mm

distance of rungs: 300 mm

thickness of metal sheet: 1,5 mm

product description: Cable ladder is designed to create a cable route. It allows you to create horizontal, vertical and inclined routes.

The cable ladder consists of sidewalls and rungs, this design allows better cooling of cables.

Perforated sidewalls create the L-profile with a bended tag. Perforated rungs of the C-profile are attached to the sidewalls by pressing through in the distance of 300 mm with the open side of the profile upwards.

The cables are fastened to the rungs using PKC 1 cable clamps.

Connection of ladders is carried out using couplings S 60X200 and using min. 4 pieces of screws NSM 6X10. Use coupling KPBSKL fully attached by screws for standardized tray.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
 F - Hot Dip Galvanized according to EN ISO 1461
 sidewalls - zinc-layer 55 µm (min. 45 µm)
 rungs - zinc-layer 45 µm (min. 35 µm)

sales amount: á 3 m

meets the requirements: EN 61537:02

classification: ČSN 73 0895 P 90-R
 DIN 4102-12 E 90
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

