



product description: intended for installation to the distribution of low voltage  
 standard shape  
 designed for wall or ceiling mounting  
 possibility to install in places with risk of flammable gases and vapor – danger zone 2  
 possibility to install in places with explosive risk of dust – danger zone 22  
 White trunkings are not a breeding ground for bacteria\* , tested in SZÚ according to ČSN EN ISO 846:2019

material: PVC - Pb-free  
 self-snuffing: yes, within 30 s  
 temperature resistance: -5 - +60 °C  
 flaming loop test: 850 °C  
 impact strength: 0,5 J  
 protection types: IP20  
 fire class for underlying material: A1-F  
 inside area: 50 mm<sup>2</sup>  
 distance base perforation: 200 ±20 mm  
 length tolerance: ±10 mm  
 weight: 0,07 kg/m  
 meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07  
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

item number	length	color	package	package - description	note
<b>LV 11X10_HD</b>	2 m	white RAL 9003	150 m	carton	-
<b>LV 11X10_P2</b>	2 m	white RAL 9003	150 m	carton	self-adhesive tape

\*List of bacteria that have been tested:  
 ESCHERICHIA COLI, STAPHYLOCOCCUS AUREUS, KLEBSIEL/A PNEUMONIAE, PSEUDOMONAS AERUGINOSA, ENTEROCOCCUS FAECALIS, BACILLUS SUBTILIS, SALMONELLA ENTERICA, LEGIONELLA PNEUMOPHILA, CANDIDA ALBICANS