

## DATA SHEET

coupling for corrugated pipes KOPOFLEX® and KOPODUR®  
and doublecoated corrugated drainage pipes DUODREN



product description: slip-over coupling is intended to connect the corrugated pipes KOPOFLEX® or KOPODUR® and for connection of DUODREN drainage pipes  
when using a sealing ring, the protection class is IP67

material: PE  
halogen-free: yes  
self-snuffing: no  
thermal resistance: -45 - +60 °C  
fire class for underlying material: A1  
UV stable: no  
protection types: IP40  
meets the requirements: EN 61386-24:11, EN 61386-1 ed.2:09  
storage: ČSN 64 0090



chemical resistance: YES: acetone, ammonia 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
NO: aniline, chlorinated hydrocarbons, tetrachlorocarbon

item number	outer Ø pipe (mm)	for pipes	fuses
<b>02040_FA</b>	40	KF 09040; KD 09040	●
<b>02050_FA</b>	50	KF 09050; KD 09050	●
<b>02063_FA</b>	63	KF 09063; KD 09063; DUODREN 63	
<b>02075_FA</b>	75	KF 09075; KD 09075; DUODREN 75	
<b>02090_FA</b>	90	KF 09090; KD 09090; DUODREN 90	●
<b>02110_FA</b>	110	KF 09110; KD 09110; DUODREN 110	
<b>02125_FA</b>	125	KF 09125; KD 09125	●
<b>02160_FA</b>	160	KF 09160; KD 09160	
<b>02200_FB</b>	200	KF 09200; KD 09200	