



product description: intended for installation to the distribution of low voltage

standard shape

designed for wall or ceiling mounting

double lock on lid increasing the trunking's rigidity and ensuring stronger cover fixation

possibility to install in places with risk of flammable gases and vapor – danger zone 2

possibility to install in places with explosive risk of dust – danger zone 22

black PVC trunkings are designed for indoor use

the _P2 configuration - adhesive tape on the back side for easier fixing of the trunking before final installation to the substrate material

material: PVC - Pb-free

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

impact strength: 0,5 J

protection types: IP40

fire class for underlying material: A1-F

inside area: 140 mm²

distance base perforation: 200 ±20 mm, Ø 4,5 mm

length tolerance: ±10 mm

weight: 0,1 kg/m

mechanical protection according to EN 50102: IK06

meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07

storage: ČSN 64 0090

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate

NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

trunkings are not a breeding ground for bacteria, tested in SZÚ according to ČSN EN ISO 846:2019

List of bacteria that have been tested:

ESCHERICHIA COLI, STAPHYLOCOCCUS AUREUS, KLEBSIELLA PNEUMONIAE, PSEUDOMONAS AERUGINOSA, ENTEROCOCCUS FAECALIS, BACILLUS SUBTILIS, SALMONELLA ENTERICA, LEGIONELLA PNEUMOPHILA, CANDIDA ALBICANS

item number	length	color	package	package - description	note
LHD 20X10_HD	2 m	white RAL 9003	96 m	carton	protective film
LHD 20X10_P2	2 m	white RAL 9003	96 m	carton	self-adhesive tape
8921_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	end
8922_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	connecting
8923_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	bending
8924_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	branching
8925_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	inner corner
8926_HB		white RAL 9003	10 / 100 / 1560 pcs	foil / foil / carton	outer corner
LHD 20X10_FD	2 m	black RAL 9005	96 m	carton	protective film
8921_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	end
8922_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	connecting
8923_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	bending
8924_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	branching
8925_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	inner corner
8926_FB		black RAL 9005	10 / 100 / 1560 pcs	foil / foil / carton	outer corner

accessories: instrument carrier QUADRO PNQ 20X10_HB

recycling symbols:



PVC trunkings, PVC covers



PCABS covers



Protective film, adhesive tape, packaging film for trunkings, bags, and packaging film for covers



cardboard

usage of inner trunking cross-section (60%):

orientation cable diameter (mm)	6	7
number of inserted cables	2	1

Risks Associated with Product Use:

During installation, use appropriate protective work equipment and follow safety guidelines

Use the product only for the purposes intended by the manufacturer

Use the product in an environment that complies with the manufacturer's instructions

Do not use the product if it is damaged

Follow the manufacturer's recommendations and do not exceed the number of inserted cables or the product's load capacity

After installation, check the correctness of the mounting of trunkings and covers according to the manufacturer's recommendations